

BANDIT

- SEMI-STATIC ROPE -
CE EN1891-A

DIAMETERS & COLORS

Ø 10,5 mm

 Ø 11 mm

LENGTH OPTIONS

20, 40, 60, 100, 200, 900 meters
Other lengths available on request

TERMINATION

Available with 1 or 2 stitched eyes

The Bandit rope brings together all the expertise of our teams. Designed in close collaboration with cavers, GRIMP rescue professionals, and rope access technicians.

Engineered for a wide range of uses, the treatment and quality of the fibers used give it lasting flexibility and knotability.

TECHNICAL SPECIFICATIONS

	Ø 10.5 mm	Ø 11 mm
Materials / Construction	32 strand Polyamide	32 strand Polyamide
Static resistance	29 kN	31 kN
Resistance with stitched eye	22 kN	23 kN
Mass per meter	68 g/m	73 g/m
Sheath percentage	37 %	34 %
Core percentage	63 %	76 %
Elongation 50/150Kg	2.3 %	2.5 %
Knotability	1	1
Retraction with water	3.6 %	3.5 %
Référence	MM400+++	ML400+++

ADVANTAGES

- Minimizes the spring effect, ideal for descent/hoisting
- Versatile, suitable for various applications
- Flexible and highly resistant to wear

