

DATASHEET

IGNITE NUCLEON



GENERAL

Art.Nr:	G-1161-M/XXL	Standards:	EN 358:2018,EN 361:2002
GTIN:	4030281008736	Net weight:	2.40 kg
E-class number:	40-21-04-01	Gross weight:	2.88 kg
Customs tariff number:	63079098		

DATASHEET

IGNITE NUCLEON

This full-featured fall arrest harness with sliding plate and climbing protection eyelet was specially developed for wind energy, but it is also used in many other areas such as telecommunication, energy supply and construction where the highest demands on safety and functionality apply. IGNITE NUCLEON scores with a breathable hip pad that distributes the load evenly on the hip and is protected against abrasion from the outside with a protective sliding plate. The correct position of the sternal and dorsal fall arrest eyelet can be perfectly adjusted to the user. Leg pads are interchangeable if required. An integrated fall indicator and innovative stainless steel OKTALOCK buckles provide additional safety. Excess webbing is no longer a nuisance thanks to practical webbing fixation. The material loops and tool eyelets offer versatile options for accommodating tools.

FEATURES

Colour:	Black, Orange, Anthracite
Attachment points:	Sternal steel attachment point, Dorsal steel attachment point, Side steel attachment point, Climbing protection steel attachment point
Number of material loops 7 kg:	2
Number of material loops 10 kg:	2
Number of material loops 15 kg:	0
Harness features:	Lanyard parking ring, Fallindicator, Wind plate
Hand wash:	40 °C
Maximum lifetime:	10 years
Minimum hip size:	85 cm
Maximum hip size:	120 cm
Minimum leg size:	75 cm
Maximum leg size:	100 cm
Min. temperature:	-35 °C
Max. temperature:	40 °C
Padding:	Back padding, Leg paddings removeable, Removeable shoulder paddings
Buckles:	stick_buckle, oktalock

DATASHEET

IGNITE NUCLEON

Adjusting buckles: Adjusting buckles shoulders, Adjusting buckles torso, Adjusting buckles hips, Adjusting buckles legs

DIMENSIONS

Size: M-XXL

MATERIAL

Material: Polyester, Aluminium, Steel, Stainless Steel
