



WORK HELMET | ABS

Safety helmet for work at height, industrial activities and building construction.

- Lightweight helmet, comfortable and well ventilated with wheel adjustment system.
- Chinstrap designed to open in the event of suspension and prevent choking: it opens between 15 and 25 daN (conform to CE EN 397 standard).
- Size adjustment wheel easily handable even with gloves on.
- Shell with ventilation holes and clips for mounting headlamps.
- Pre-drilled holes for the installation of the visor and ear muffs (optional).
- Internal webbing suspension system with removable and washable padding.
- Available in various colors (white, yellow, red, black and high visibility) also with special rubberized black finishing "Soft Touch"
- HV version (high visibility) in yellow fluo with reflective stickers.
- Reflective versions dedicated to medical emergency and public assistance, in red or white with reflective stickers for night visibility.
- Universal size (52-64 cm).
- High quality product, made in Italy!


Lifetime and Inspections



Usage activities

SCAFFOLDING AND TRESTELS	ROOF AND INCLINED PLANES	METAL STRUCTURES	ROPE ACCESS
CONFINED SPACES	LADDERS AND ELEVATING PLATFORMS	TREECLIMBING / ARBORICULTURE	
FIREBRIGADES AND CIVIL PROTECTION	HELIRESCUE	WIND TURBINES	WATER DANGER

ITEM CODES

Item	Standards	Material	Colour	 (g)	Size	Circumference (cm)	Notes
99718AN02KK	EN 397 EAC	ABS	Black	385	UNI	52-64	
99718GN02KK	EN 397 EAC	ABS	Matte Black	385	UNI	52-64	
99718AY02KK	EN 397 EAC	ABS	Yellow	385	UNI	52-64	
99718AO02KK	EN 397 EAC	ABS	Orange	385	UNI	52-64	
99718AW02KK	EN 397 EAC	ABS	White	385	UNI	52-64	
99718AR02KK	EN 397 EAC	ABS	Red	385	UNI	52-64	
99718AA02KK	EN 397 EAC	ABS	Blue	385	UNI	52-64	
99718RO02KK	EN 397 EAC	ABS	Orange Fluo Reflective Soft Touch	385	UNI	52-64	
99718RY02KK	EN 397 EAC	ABS	Yellow Fluo Reflective Soft Touch	385	UNI	52-64	
99718FR02KK	EN 397 EAC	ABS	Red Reflective	385	UNI	52-64	
99718FW02KK	EN 397 EAC	ABS	White Reflective	385	UNI	52-64	
99718FY02KK	EN 397 EAC	ABS	Yellow Fluo Reflective	385	UNI	52-64	

Copyright © KONG spa | P.IVA 00703180166
Via XXV Aprile, 4 23804 Monte Marenzo (LC) Italy | Tel. +39 0341 630506